

# OPTIMUS SUPER EXTRA 10W-40

Synthetic Technology Gasoline Engine Oil SAE 10W-40 SL

## Description

**OPTIMUS SUPER EXTRA 10W-40** is a synthetic technology gasoline engine oil designed to lubricate cars of the latest model even when they are operating under the severest conditions. It is formulated from oil with detergent-dispersant, anti-rust, oxidation inhibitors, high viscosity index and low foaming tendency.

## Applications

**OPTIMUS SUPER EXTRA 10W-40** is recommended for use in new gasoline cars technology especially turbocharger and multi-valve system engines where API service SL lubricant is required.

## Specification Meets:

**OPTIMUS SUPER EXTRA 10W-40** meets API Service SL specification.

## Advantages

- ▶ Good thermal and oxidation stability
- ▶ Elimination carbon deposits
- ▶ Good rust and corrosion protection
- ▶ Good engine cleanliness
- ▶ Long term wear protection of the engine part

## Typical Data of OPTIMUS SUPER EXTRA 10W-40

Characteristics	Unit	OPTIMUS SUPER EXTRA 10W-40	Test Method
Color		L 2.5	ASTM D 1500
Density @ 15 °C	kg/L	0.8546	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	95.74	ASTM D 445
Kinematic Viscosity @ 100 °C		14.48	
Viscosity Index		157	ASTM D 2270
Flash Point (COC)	°C	232	ASTM D 92
Pour Point	°C	-27	ASTM D 97
CCS Viscosity @ °C	cP	4847 (-25)	ASTM D 5293
Sequence I : 24 °C	mL	0/0	ASTM D 892
Sequence II : 93.5 °C		0/0	
Sequence III : 24 °C after 93.5 °C		0/0	

\* the typical characteristic mentioned represent mean values