

ROLLA RL 150

Circulating oil for specialized metalworking application

Description

ROLLA RL 150 is a high quality paraffinic base oil with anti-rust additives, oxidation inhibitors, and low foaming tendency. The product is also formulated with antioxidant and antirust additives.

Advantages

- ▶ Good rust and corrosion protection
- ▶ Good thermal and oxidation stability
- ▶ Excellent water-separability
- ▶ Compatible with seals

Applications

ROLLA RL 150 is recommended for the application of normal load and temperature with system splash or circulation lubrication for use in gear, rolling, and circulating systems.

Specification Meets:

ISO-L-CKB, DIN 51524 TEIL 1 HL.

Typical Data of ROLLA RL 150

Characteristics	Unit	ROLLA RL 150	Test Method
Color	kg/L	L 0.5	ASTM D 1500
Density @ 15 °C	kg/L	0.895	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	148.5	ASTM D 445
Kinematic Viscosity @ 100 °C		15.5	
Viscosity Index		107	ASTM D 2270
Flash Point (COC)	°C	254	ASTM D 92
Pour Point	°C	-12	ASTM D 97
Sequence I : 24 °C	mL	0/0	ASTM D 892
Sequence II : 93.5 °C		10/0	
Sequence III : 24 °C after 93.5 °C		0/0	

* the typical characteristic mentioned represent mean values