UNITRANS UTTO

Universal tractor transmission oil



Description

UNITRANS UTTO is a high quality heavy duty lubricant for use of most agricultural tractors and off-road equipments such as public work or handling equipments.

Applications

UNITRANS UTTO is recommended for automatic, torque converting, or hydrostatic transmissions, that require a GL-4, 10W-30 or 80W level lubricant. Also excellent for hydraulic systems, oil immersed or wet systemised brakes.

Specification Meets:

Meets the requirement of applications where Allison C-4 tpe fluids are needed. Also meets the API Gear Perfomance GL-4 specification, Volvo WB 101, John Deere JDM J 20C, CNH MAT 3525, Case MS 1207, 1209, and certain Caterpillar and Komatsu machines. Please contact us for more detailed specification.

Advantages

- Excellent oxidation stability
- Excellent performance at low or high temperature
- Very good shear stability and anti-form characteristics
- Very good extreme pressure and antiwear properties

Typical Data of UNITRANS UTTO

Characteristics	Unit	UNITRANS UTTO	Test Method
Density @ 15 °C	kg/L	0.8820	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	160	ASTM D 445
Kinematic Viscosity @ 100 °C		10.2	
Viscosity Index		160	ASTM D 2270
Flash Point (COC)	°C	220	ASTM D 97
Pour Point	°C	-39	ASTM D 92

^{*} the typical characteristic mentioned represent mean values

PT PANA OIL INDONESIA

customersupport@panaoil.id www.panaoil.id

Page 1/1 ver. 160215