GOTRA TM

Mineral oil based transmission oil



Description

GOTRATM is a high performance heavy duty gear oil, formulated with high quality raw material and selected additives such as the high quality sulfur-phosphorus extra pressure additive anglamol ensuring maximum lubrication.

Applications

GOTRA TM is used for lubrication of hypoid or spiral bevel gears in transmissions, gearboxes and steering systems in heavy duty vehicles.

Specification Meets:

GOTRA TM meets API service GL-5, MTI performance standards.

Typical Data of GOTRA TM

Characteristics	Unit	GOTRA TM		Test Method
		80W-90	140	rest Method
Color		Light Brown	Light Brown	ASTM D 1500
Density @ 15 °C	kg/L	0.8944	0.9013	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	189.60	415.80	ASTM D 445
Kinematic Viscosity @ 100 °C		17.60	29.70	
Viscosity Index		109	98	ASTM D 2270
Flash Point (COC)	°C	205	238	ASTM D 92
Pour Point	°C	-30	-12	ASTM D 97
Sequence I: 24 °C	mL	0/0	0/0	ASTM D 892
Sequence II: 93.5 °C		0/0	0/0	
Sequence III : 24 °C after 93.5 °C		0/0	0/0	

^{*} the typical characteristic mentioned represent mean values

Page 1/1 ver. 150724